

Project Name:	SIA#
Location:	
Item #: Qty:	AIA#
Model #:	

Model:

DR54F

Frezeers - Solid Door Reach In 2 solid doors frezeer 41 ft3





Opp

Features & Benefits

Strong & Durable Structure

- Stainless steel interior and exterior.
- Aluminum back exterior.

Temperature

• Temperature range -7°F~0°F (-22°C~-18°C).

User Friendly Features

- Self-closing solid doors with 90 degrees stay open feature. Locks and keys included.
- Recessed handles for ease of opening and cleaning.
- Adjustable heavy duty PVC coated shelves.
- Easy access to condenser coil for cleaning and service.
- Easy adjust temperature set point and defrost frequency.

Pre-installed heavy-duty casters with brakes. Refrigerant R290.

Y	Certifications

Intertek Intertek

Daara	Chalusa	LID	ANADO	ANADO Constantinuativista		ensions (inch	nes)	
Doors	Shelves	HP	AMPS Crated Weig	P AMPS	Crated Weight	W	D	Н
2	6	12/7	8.5	451 Lb (205 Kg)	54" (1371 mm)	32.20" (818 mm)	82.50" (2095 mm)	

Packaging dimensions: W 56.5" (1435 mm) x D 33.4" (880 mm) x H 84.4" (2145 mm).


Approvals:	Available At:

Frezeers - Solid Door Reach In

2 solid doors frezeer 41 ft³



Front View



Side View





Electric Data				
Voltage	115/60/1			
Plug Type	NEMA 5-15P			
Compressor HP	1			
Refrigerant	R290			

Dimensional Data			
Capacity - cu. ft.	41 ft³ (1169 liters)		
Net Weight - Lbs.	446.6 Lbs. (203 Kg)		

Slight Variations May Exist