

SIA
AIA

Model:

DRF40-LP

Fryer
40 Lb / 21 L - Propane Gas





Opp

Features & Benefits

Strong & Durable Structure

- Heats oil quickly to produce better-tasting food with less oil absorption.
- Pilot light for easy fryer ignition.
- Stainless steel front, door and front ledge.
- · Galvanized steel sides and back ledge.
- Stainless steel legs.

Burners:

- Cast iron burners with a capacity of 35,000 Btu/hr.
- · Fast temperature recovery.
- Safety valve that shuts off 100% of the gas flow.
- The heat from the burners is transferred through ducts along the fryer.

Fry Pot:

- · Stainless steel structure.
- Smooth finish for easy cleaning.
- Nickel-plated grill inside.
- 1 1/4 inch (31.8 mm) full-flow drain valve for quick and secure drainage.
- Stainless steel basket support.
- 2 nickel-plated frying baskets included, with heat-insulated grip area coating.

Thermostat:

- Thermostat imported and CSA certified.
- Safety shut-off valve.
- 200°F ~ 400°F (93°C ~ 204°C).

✓	Certifications			
	NSF Intertek			
	22/04/2024			

Approvals: Available At:


DRF40-LP

Fryer 40 Lb / 21 L - Propane Gas

Burners	Gas	Capacity	Fry	yer Dimens	sions	Bas	sket Dimens	sions	Net Weight
	Output	Dutput		W	Н	L	W	π	not weight
3	105,000 Btu/hr	44 Lb (21 L)	15.5" (394 mm)	29.6" (753 mm)	43.8" (1114 mm)	12.1" (308 mm)	6.2" (160 mm)	5.3" (136 mm)	110 Lb (50 Kg)



Front View



Side View





Gas Specifications:				
Gas Type:	Propane gas			
Manifold pressure:	11" W.C.			
Gas connection:	3/4"			
*Specify type of gas and elevation if over 2000 ft.				

Packaging data:			
Dimensions:	L 18" (450 mm) W 35" (890 mm) H 35" (890 mm)		
Crated weight:	121 Lb (55 Kg)		

Slight Variations May Exist.