

Project Name:	SIA
Location:	
Item #: Qty:	AIA
Model #:	'''' '

Model:

DRF75-LP

Fryer
75 Lb / 35 L - Propane Gas





O

Features & Benefits

Strong & Durable Structure

- Heats oil quickly to produce better-tasting food with less oil absorption.
- Pilot light for easy fryer ignition.
- Stainless steel front, door and front ledge.
- Galvanized steel sides and back ledge.
- Stainless steel legs.

Burners:

- Cast iron burners with a capacity of 35,000 Btu/hr.
- Fast temperature recovery.
- Safety valve that shuts off 100% of the gas flow.
- The heat from the burners is transferred through ducts along the fryer.

Fry Pot:

- Stainless steel structure.
- Smooth finish for easy cleaning.
- Nickel-plated grill inside.
- 1 1/4 inch (31.8 mm) full-flow drain valve for quick and secure drainage.
- Stainless steel basket support.
- 2 nickel-plated frying baskets included, with heat-insulated grip area coating.

Thermostat:

- Thermostat imported and CSA certified.
- Safety shut-off valve.
- 200°F ~ 400°F (93°C ~ 204°C).

Certifications



22/04/2024

Approvals: Available At:


DRF75-LP

Fryer 75 Lb / 35 L - Propane Gas


Burners	Gas Capacity		Fry	er Dimens	ions	Bas	ket Dimens	ions	Net Weight
Barriers	Output	L	W	Η	L	W	Н	word wording	
5	175,000 Btu/hr	72 Lb (35 L)	20.1" (510.8 mm)	34.8" (886 mm)	44.2" (1124 mm)	12.1" (308 mm)	6.2" (160 mm)	5.3" (136 mm)	154 Lb (69.8 Kg)



Front View



Side View





Gas Specifications:			
Gas Type:	Propane gas		
Manifold pressure:	11" W.C.		
Gas connection:	3/4"		
*Specify type of gas and elevation if over 2000 ft.			

Packaging data:			
Dimensions:	L 22" (558 mm) W 40" (1016 mm) H 36" (914 mm)		
Crated weight:	165 Lb (74.8 Kg)		

Slight Variations May Exist.